




BASE PLATE SECTION




POLE JOINTS



POLE NUMBER LOCATIONS




MAST ARM CONNECTION



FOUNDATION SECTION

FOUNDATION NOTES

1. 3000 P.S.I. CLASS A CONCRETE PLACED NEXT TO UNDISTURBED EARTH.
2. 4 - 7/8 " x 36" GALVANIZED ANCHOR BOLTS WITH LEVELING NUTS & WASHERS. TACK WELD NUTS TO WASHERS AND WASHERS TO BASE PLATE AFTER TIGHTENING. (2 1/2 " PROJECTION)
3. 1 1/2 " THICK EMBECO GROUT #636 OR APPROVED EQUAL.
4. UNSTABLE SOILS, AND/OR POLE HEIGHTS OVER 40', SHALL REQUIRE SPECIAL ENGINEERING.
5. A 25' COIL OF NO. 4 STRANDED A.W.G. BARE COPPER CONDUCTOR SHALL BE INSTALLED BEFORE THE CONCRETE IS POURED. IT SHALL BE CONNECTED TO POLE GROUNDING SCREW IN THE BASE OF THE POLE.
6. ALL FINISHED POLE FOUNDATIONS SHALL BE CHAMFERED, AND AT SIDEWALK GRADE UNLESS OTHERWISE NOTED.
7. THIS FOUNDATION MAY ALSO BE USED FOR DUAL MAST ARM POLES.



PENETRATIONS

DETAIL NO.
G-3291-2

**CITY OF GOODYEAR
STANDARD DETAIL**

APPROVED BY:
Goodyear Standards and
Policies Committee 7/97

STREAMLINE STEEL POLE DETAILS
(FOR USE IN AREAS DESIGNATED BY PUBLIC WORKS DIRECTOR.)

DETAIL NO.
G-3291-2